

Solis

FUTURE IS NOW

120.20



6 CYLINDER HIGH TORQUE TURBO ENGINE



AERODYNAMIC BONNET



4WD HEAVY DUTY FRONT AXLE



QUAD PROJECTOR LAMPS



LONGER WHEEL BASE & HEAVY WEIGHT TRACTOR FOR BETTER STABILITY



OPEN & WIDER PLATFORM



24+24 SYNCHRO SHUTTLE TRANSMISSION











HYDRAULIC LIFTING CAPACITY 4500 KG









SHUTTLE XL

SUPER SYNCHRO >>> GEAR SHIFT ON THE GO >>>

www.solistractores.mx

FEATURES	SOLIS 120.20 CABIN
ENGINE 	
Engine Type	6 Cylinder Turbocharged Engine
HP Category	125 HP Category
Emission	Stage II
No of Cylinder	6
Aspiration	Turbocharged with Intercooler
Cubic Capacity	6127 cc
Bore/Stroke	105/118
Rated RPM	2200
Air Cleaner	2 Stage Dry Type
Cold Start	Yes
Max Torque (Nm)	475 (±5%)
TRANSMISSION 	
Drive	4WD
Gearbox	Synchromesh
Clutch	Double Clutch
No of Speeds	24Forward + 24Reverse
SPEED (FORWARD) 	
Minimum Speed (km/hr)	0.57 Kmph (Varies with Tires)
Maximum Speed (km/hr)	36.6 Kmph (Varies with Tires)
BRAKES 	
Brakes	Oil Immersed
Type of Brake Actuation	Hydraulic Assisted Brakes
Parking Brake	Independent Lever
Trailer Brake	HTB (Standard)
Differential Lock	Electrical Switch Operated
PTO 	
PTO (RPM)	Rear-540 & 540E 540 & 1000 (optional)
PTO (Actuation)	Mechanical Lever Operated
STEERING 	
Steering	Power Steering
ELECTRICALS 	
Battery	12v, 110 Ah
Alternator	12V, 90 Amp
Seven Pin Trailer Socket	Yes
SAFETY SWITCHES 	
Neutral Safety Switch	Standard
PTO Safety Switch	Standard
Clutch Safety Switch	Standard

FEATURES	SOLIS 120.20 CABIN
HYDRAULICS 	
Position & Draft Control	Electronic Lift (EHR)
Litre Per Minute (LPM)	75
3 Point Linkage	CAT II
Auxiliary Hydraulic Circuit	3DA,2SA WITH I Detent
Lift Capacity	4500 Kg
CAPACITY (LITRES ±6%) 	
Fuel Tank	150
TYRE 	
Front	380/85R24
Rear	460/85R34
OVERALL DIMENSIONS 	
Weight (Kg)	4285
Wheel Base (mm)	2655
Total Length (mm)	4660
Total Width (mm)	2260
Height (mm)	2660
Min. Ground Clearance	460
Front Track (mm)	1760
Rear Track (mm)	1720
Turning Radius (mm)	6770 (w/o brake)
OTHERS 	
Drawbar	Yes, Ladder Hitch
ROPS	Standard
Canopy	Standard
Cabin	Optional
STD. Ballast Weight	Front - 72kg Base weight 31*10 Rear-40*1 on each wheel
Front Tow Hook	Standard
OPTIONAL FEATURES 	
Weight Optional	Front - 31*8
Front Mudguard	Optional
Tyre Options	Front: 14.9x 24 Rear: 18.4 x 34

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

Solis 120.20 CABIN tractor is designed for all terrains. A powerful engine, long operating range and durability ensures you get the job done, no matter what it takes. With exceptional support and unmatched performance, Solis 120.20 CABIN can make all your ventures successful. Discover the machine that is built to last.



Dealership stamp

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax: +91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractores.mx