

Solis

FUTURE IS NOW

2020



3 CYLINDER DIESEL ENGINE



**ADVANCE EUROPEAN
AERODYNAMIC STYLING**



**FRONT TOW HOOK
STANDARD**



**STYLISH TWIN PROJECTOR
LAMPS**



FOLDABLE ROPS



**OPEN & WIDER
PLATFORM**



POWER STEERING



**HYDRAULIC LIFTING
CAPACITY 500KG**



www.solistractores.mx

FEATURES	Solis 2020
ENGINE	
Engine Type	MHI
HP Category	20
No. of Cylinders	3
Aspiration	Natural
Cubic Capacity (cc)	952
Rated RPM	2700
Air Cleaner	Dry Type with Clogging Sensor
Cold Start	Standard
Max Torque @ RPM (Nm)	50 Nm
Exhaust	Downdraft Exhaust
TRANSMISSION	
Drive	4WD
Clutch	Single Clutch
Gearbox	6F+2R
Front Axle	4WD
Transmission	Sliding Mesh
SPEED (FORWARD) (AGRI)	
Maximum Speed (Km/Hr)	13.93 @ fullfly up
Minimum Speed (Km/Hr)	1.3 @ 2700 erpm
BRAKES	
Brakes	Dry Drum Brakes
Type of Actuation	Mechanical
Parking Brake	Independent
DIFFERENTIAL LOCK	
Differential Lock	Mechanical, Foot Operated
PTO	
PTO (RPM)	540/1000
PTO (Actuation)	Mechanical
STEERING	
Steering	Mechanical/Power Steering (Optional)
ELECTRICAL	
Battery	12V, 65Ah
Alternator	12V, 42Amp
Seven Pin Trailer Socket	Output 12V
HYDRAULICS	
3 Point Linkage	Cat 1-N
Stay Bars	Anchor Chain
Hydraulic Lifting Capacity (Kg)	500
Auxiliary Hydraulic Circuit	1DA / 1SA (optional)
Lift Rods	Single Arm Adjustable

FEATURES	Solis 2020			
SAFETY SWITCH				
Clutch Safety Switch	Standard			
PTO Safety Switch	Standard			
Neutral Safety Switch	Standard			
CAPACITY (Ltrs.) (+/-5%)				
Fuel tank (Ltr.)	26			
TURNING RADIUS				
Without Brakes (m)	2.7 - 3.0			
TYRE				
Front	5-12			
Rear	8-18			
DIMENSION & WEIGHT (+/-5%)				
Weight (kg)	935			
Wheel Base (mm)	1420			
Overall Length (mm)	2735			
Overall Width (mm)	930-1180			
Height (mm) Up to ROPS	1945			
Min. Ground Clearance (mm)	200			
Front Track (mm)	781			
Rear Track (mm)	724			
OTHERS				
Fuel Indicator Gauge	Standard			
Front Tow Hook	Standard			
Front & Rear Weights with std. Ballast	2 x 15kg Front Dead Weights			
Trailer Hitch	1. Swinging Bar (Optional) 2. Clevis Hitch (Standard) 3. Semi Automatic Hitch			
Roll Over Protection	Standard			
OPTIONAL FEATURES				
TYRES				
TURF Front Tyre: 23x8.50-12 Rear Tyre: 33x15.50-16.5	INDUSTRIAL Front Tyre: 23x8.50-12 Rear Tyre: 33x15.50-16.5	AGRI Front Tyre: 6x12 Rear Tyre: 8.3x20	RADIAL Front Tyre: 6.5/80-12 Rear Tyre: 280/70 R18	GALAXY PRO Front Tyre: 220/55 R12 Rear Tyre: 280/70 R16
Front End Loader	Optional			

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

The sub compact low noise and environment-friendly Solis 2020 is the dependable performer for every field. Bringing in the marvel for better productivity, this innovative tractor transcends the boundaries of limits to deliver top quality performance. The highly competent 500 kg lifting capacity is the best in class facility that is available to the farmers. Fully powered in aerodynamic design with projector lamps, Solis 2020 facilitates maximum traction on the field with operator control.



Dealership stamp

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax: +91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.mx