

**Solis**

# **FUTURE IS NOW**

HEAVY DUTY 4 CYLINDER  
TURBOCHARGED ENGINE



ADVANCE EUROPEAN  
AERODYNAMIC STYLING



FACTORY FITTED  
FRONT WEIGHTS



STYLISH TWIN  
PROJECTOR WITH DRL



LONGER WHEEL BASE & HEAVY  
WEIGHT TRACTOR FOR BETTER  
STABILITY



CONSTANT MESH  
TRANSMISSION



FLAT FLOOR &  
WIDER PLATFORM



HYDRAULIC LIFTING  
CAPACITY 2000KG



















**7520**



**SUPER  
YNCHRO** >> GEAR SHIFT ON THE GO >>

[www.solistractores.mx](http://www.solistractores.mx)

| FEATURES   |  | Solis 7520                      |
|--|--|---------------------------------|
| <b>ENGINE</b>             |  |                                 |
| HP Category  |  | 75                              |
| Emission   |  | Stage 2 / Stage 3               |
| No. of Cylinders   |  | 4                               |
| Aspiration   |  | Turbocharged                    |
| Cubic Capacity (cc)  |  | 3707                            |
| Rated RPM  |  | 2200/2000                       |
| Air Cleaner  |  | Dry Air Cleaner                 |
| Cold Start   |  | Standard                        |
| Max Torque (Nm)  |  | 278 Nm @1200   289 Nm @1300     |
| Exhaust  |  | Upward                          |
| Muffler  |  | Underhood                       |
| <b>TRANSMISSION</b>       |  |                                 |
| Drive  |  | 4WD / 2WD                       |
| Clutch   |  | Dual Clutch, Dry Friction Plate |
| Gearbox  |  | 8F+2R                           |
| Front Axle   |  | 4WD                             |
| Transmission   |  | Constant Mesh                   |
| <b>SPEED (FORWARD)</b>    |  |                                 |
| Maximum Speed (Km/Hr)  |  | 36.46 @ 2200 erpm               |
| Minimum Speed (Km/Hr)  |  | 1.95 @ 2200 erpm                |
| <b>BRAKES</b>             |  |                                 |
| Brakes   |  | Oil Immersed Brake              |
| Type of Actuation  |  | Mechanical                      |
| Parking Brake  |  | Independent Type                |
| <b>DIFFERENTIAL LOCK</b>  |  |                                 |
| Differential Lock  |  | Mechanical, Foot Operated       |
| <b>PTO</b>               |  |                                 |
| PTO (RPM)  |  | 540@1680                        |
| PTO (Actuation)  |  | Mechanical                      |
| <b>STEERING</b>         |  |                                 |
| Steering   |  | Power                           |
| <b>ELECTRICAL</b>       |  |                                 |
| Battery  |  | 12V, 110 AH                     |
| Alternator   |  | 12V, 36Amps                     |
| Seven Pin Trailer Socket   |  | Output 12V                      |
| <b>HYDRAULICS</b>       |  |                                 |
| 3 Point Linkage  |  | CAT-II                          |
| Hydraulic Lifting Capacity (kg)  |  | 2000                            |
| Auxiliary Hydraulic Circuit  |  | 2DA                             |

| FEATURES  |  | Solis 7520                               |
|---|--|--|
| <b>SAFETY SWITCH</b>                   |  |  |
| Neutral Safety Switch   |  | Standard                                 |
| <b>CAPACITY (Ltrs.) (+/-5%)</b>        |  |  |
| Fuel Tank (Ltr.)  |  | 65                                       |
| <b>TURNING RADIUS</b>                  |  |  |
| Without Brakes (m)  |  | 5.34                                     |
| <b>TYRE</b>                            |  |  |
| Front   |  | 11.2x24 (4WD)                            |
| Rear  |  | 16.9x30                                  |
| <b>DIMENSION &amp; WEIGHT (+/-5%)</b>  |  |  |
| Weight (kg)   |  | 3120                                     |
| Wheel Base (mm)   |  | 2310                                     |
| Total Length (mm)   |  | 4190                                     |
| Total Width (mm)  |  | 1980                                     |
| Height (mm) Up to ROPS  |  | 2710                                     |
| Min. Ground Clearance (mm)  |  | 400                                      |
| Front Track (mm)  |  | 1670                                     |
| Rear Track (mm)   |  | 1500                                     |
| <b>OTHERS</b>                          |  |  |
| Fuel Indicator Gauge  |  | Standard                                 |
| Front Tow Hook  |  | Standard, Inbuilt in Front Weights       |
| Standard Weight (kg)  |  | Front 30x2+25x4   Rear 1x34 on Each Tyre |
| ROPS  |  | Standard                                 |
| Canopy  |  | Standard                                 |
| <b>OPTIONAL FEATURES</b>               |  |  |
| Cabin   |  | Optional                                 |
| Tyre  |  | Front Tyre: 7.5x16   Rear Tyre: 16.9x30  |

### Solis 7520 Non Turbo Engine

|                     |                    |
|---------------------|--------------------|
| Aspiration          | Natural Aspiration |
| Emission            | Stage 2            |
| Max. Torque (Nm)    | 272 @ 1300         |
| Rated RPM           | 2200               |
| Cubic Capacity (cc) | 4087               |

\*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All Dimensions are with standard tyres.

Elevate your everyday farming into an extraordinary journey with the Solis 7520. Engineered with best-in-class mechanics, it empowers farmers to go beyond the ordinary. Equipped with a powerful 4-cylinder turbocharged engine, a lifting capacity of up to 2000 kg, and unmatched versatility across all implements and applications, this advanced tractor ensures superior ergonomics and effortless manoeuvrability in every soil condition.



Dealership stamp

INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)  
 Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221  
 Fax: +91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractores.mx